




White CAT6 Cable 0.5m (1.6ft)

TC 0.5MCAT6 EU SAP: 3265140 US SAP: 12939555

vav.link/tc_0-5mcat6

VISION



IMAGE

Product Images

ZIP 813.30 KB

files.visionaudiovisual.com/products/TC_0-5MCAT6/images/TC_0-5MCAT6.zip

Product Images

PNG 3.01 KB

files.visionaudiovisual.com/products/TC_0-5MCAT6/images/TC-CAT6.png

Product Images

PNG 834.77 KB

files.visionaudiovisual.com/products/TC_0-5MCAT6/images/TC_0.5MCAT6.png

SPECIFICATIONS

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.04 kg (0.09 lb)

PACKAGED DIMENSIONS

170 mm x 220 mm (6.6" x 8.6")

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS