






## White CAT6 Cable 1m (3.2ft)

TC 1MCAT6 EU SAP: 3265141 US SAP: 12939580

[vav.link/tc\\_1mcat6](http://vav.link/tc_1mcat6)

VISION



## IMAGE

Product Images

**ZIP 813.29 KB**

[files.visionaudiovisual.com/products/TC\\_1MCA66/images/TC\\_1MCA66.zip](https://files.visionaudiovisual.com/products/TC_1MCA66/images/TC_1MCA66.zip)

Product Images

**PNG 3.01 KB**

[files.visionaudiovisual.com/products/TC\\_1MCA66/images/TC-CAT6.png](https://files.visionaudiovisual.com/products/TC_1MCA66/images/TC-CAT6.png)

Product Images

**PNG 834.77 KB**

[files.visionaudiovisual.com/products/TC\\_1MCA66/images/TC\\_1MCA66.png](https://files.visionaudiovisual.com/products/TC_1MCA66/images/TC_1MCA66.png)

## SPECIFICATIONS

### INSULATION

HDPE, diameter: 0.97 mm (0.04")

### SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

### CONDUCTOR THICKNESS

24AWG (7/0.2)

### BANDWIDTH

250MHz

### IMPEDANCE ( $\Omega$ )

100±15

### DELAY SKEW @ 20°C(NS/100M)

≤45

### PACKAGED WEIGHT

0.06 kg (0.13 lb)

### PACKAGED DIMENSIONS

170 mm x 220 mm (6.6" x 8.6")

### U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS