






White CAT6 Cable 3m (9.8ft)

TC 3MCAT6 EU SAP: 3265146 US SAP: 12939582

vav.link/tc_3mcat6

VISION



IMAGE

Product Images

ZIP 813.29 KB

files.visionaudiovisual.com/products/TC_3MCAT6/images/TC_3MCAT6.zip

Product Images

PNG 3.01 KB

files.visionaudiovisual.com/products/TC_3MCAT6/images/TC-CAT6.png

Product Images

PNG 834.77 KB

files.visionaudiovisual.com/products/TC_3MCAT6/images/TC_3MCAT6.png

SPECIFICATIONS

INSULATION

HDPE, diameter: 0.97 mm (0.04")

SHEATH

PVC, thickness: 0.6 mm (0.02"); outer diameter: 6.2 mm (0.24")

CONDUCTOR THICKNESS

24AWG (7/0.2)

BANDWIDTH

250MHz

IMPEDANCE (Ω)

100±15

DELAY SKEW @ 20°C(NS/100M)

≤45

PACKAGED WEIGHT

0.14 kg (0.3 lb)

PACKAGED DIMENSIONS

220 mm x 270 mm (8.6" x 10.6")

U/UTP (UNSCREENED)

STRANDED BARE COPPER CONDUCTORS

GOLD-PLATED RJ45 BOOTED CONNECTORS